

— LED OPERATORY LIGHT

Vivid LED

Post- or ceiling-mounted LED light with a wide 3,000–35,000 lux dimming range, a PoliBlock filter mode for composite work, and motion-sensor plus manual toggle control as standard.

L700-LED shown



3K–35K_{lux}

Adjustable intensity at 700 mm

100×180

Illumination area (mm) at 700 mm

24_v

AC/DC operation

2_{year}

Warranty

STANDARD FEATURES

- ✓ Motion sensor and manual toggle
- ✓ PoliBlock filter mode for composites
- ✓ Dimmer mode, 3,000–35,000 lux
- ✓ Static heat sink cooling, no fan
- ✓ 24 V AC/DC operation
- ✓ Post mount or ceiling mount

Specifications

01 SPECIFICATIONS

Light intensity	3,000 – 35,000 lux @ 700 mm
Dimmer mode	3,000 – 35,000 lux
Illumination area	100 × 180 mm @ 700 mm
Input voltage	110V / 220V, 60 / 50 Hz
Output voltage	24 V AC / DC
Cooling	Static heat sink, no fan
Controls	Motion sensor + manual toggle
Filter mode	PoliBlock
Warranty	2 years

03 OPTIONS

RLL-PS	Power supply, 110–240 V in / 24 V out
LP-48	48" light post
L690-08	Ceiling post, 8' ceiling
L690-09	Ceiling post, 9' ceiling
L690-010	Ceiling post, 10' ceiling
L690-011	Ceiling post, 11' ceiling (special order)

02 MODELS



L700-LED

Post mount

L795-LED

Ceiling mount

Specify 8', 9' or 10' ceiling for the L795-LED. The LP-48 light post must be ordered if the light is ordered separately.

04 PACKING DIMENSIONS

Carton	L × W × H in	Weight
L700-LED	38 × 17 × 15	10 lb
L795-LED	38 × 17 × 15	18 lb
Light head	14 × 9 × 14	7 lb
L900-08 post, 8' ceiling	15 × 3 × 3	3 lb
L900-09 post, 9' ceiling	30 × 3 × 3	5 lb
L900-10 post, 10' ceiling	44 × 4 × 4	7 lb

05 COMPARE THE TPC LED LIGHT LINE

	 Vivid L700-LED	 Lustrous L550-LED	 Lucent L600-LED	 Luminous L-7601-LED	 Radiant R6101-LED
Intensity (lux)	3,000–35,000	8,000–30,000	3,000–35,000	3,000–35,000	3,000–35,000
Motion sensor	Standard	Standard	L625 / L695	L-7605	R6105
PoliBlock filter	Yes	Yes	—	Optional	—
Ceiling mount	L795-LED	L570-LED	L690 / L695	L-7901-LED	—